



NOTES

- ALL VALUES ASUME LHV OF THE GAS. 100% LOAD TOLERANCES:
 FUEL CONSUMPTION +5%,
 COOLING CIRCUIT AND EXHAUST GASES ± 8%, RADIATION ±25%
 EXHAUST TEMPERATURE ±20°C, MASS FLOWS ± 10% (ALSO FOR CO2 FLOW IN EXHAUST).
- THE ENGINE PERFORMANCE DATA, TIMING ADVANCE AND CARBURETION SETTINGS ARE VALID FOR A GAS THAT FULFILLS THE REQUIREMENTS DEFINED IN IC-G-D-30-001e AND IC-G-D-30-002e
- NET POWER, MECHANICAL PUMPS NOT INCLUDED.
- POWERS ARE VALID FOR AMBIENT TEMP.=25°C AND AN ALTITUDE OF =500 m. SEE OTHER CONDITIONS IN PI IC-G-B-00-001
- OVERLOAD NOT ALLOWED. IT IS NOT RECOMMENDED TO OPERATE BELOW 40% LOAD DURING LONG TIME.
- THE SPECIFICATIONS AND MATERIALS ARE SUBJECT TO CHANGE WITHOUT NOTIFICATION
- A ENGINE WITH INLET OR OUTPUT RESTRICTION OVER PUBLISHED LIMITS, OR WITH INADEQUATE MAINTENANCE OR INSTALLATION CAN MODIFY POWER RATING DATA.
- EMISSIONS ARE CORRECTED TO 5% OF O2. EMISSIONS ACCORDING TO D1 CYCLE IS 8178-4. (0°C and 1013 mbar)
- ALTERNATOR VOLTAGE 400 V